

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Super Lube® Fire Resistant Hydraulic Fluid**
- **Article number:** No other identifiers
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Hydraulic fluid
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Synco Chemical Corporation  
24 DaVinci Dr., P.O. Box 405  
Bohemia, NY 11716  
Telephone: 631-567-5300  
Email: info@super-lube.com
- **1.4 Emergency telephone number:**  
CHEMTREC  
1-800-424-9300 (US/Canada)  
+01 703-527-3887 (International)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EU) No 2015/830**  
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



health hazard

STOT RE 2 H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

# Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 1)

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS05 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

ethanediol

2-dimethylaminoethanol

2,2'-oxybisethanol

- **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- **Precautionary statements**

P260 Do not breathe mist/vapours/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362 Take off contaminated clothing and wash before reuse.

P314 Get medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

# Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

Trade name: Super Lube® Fire Resistant Hydraulic Fluid

(Contd. of page 2)

- **Hazard description:**
- **WHMIS-symbols:**  
D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



\* - Indicates a long term health hazard from repeated or prolonged exposures.

- **HMIS Long Term Health Hazard Substances**

None of the ingredients are listed.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 107-21-1 EINECS: 203-473-3 Index number: 603-027-00-1	ethanediol ----- ⚠ STOT RE 2, H373 ⚠ Acute Tox. 4, H302	25-50%
CAS: 111-46-6 EINECS: 203-872-2 Index number: 603-140-00-6	2,2'-oxybisethanol ----- ⚠ STOT RE 2, H373 ⚠ Acute Tox. 4, H302	10-25%

(Contd. on page 4)

# Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

Trade name: Super Lube® Fire Resistant Hydraulic Fluid

(Contd. of page 3)

CAS: 67762-36-1 EINECS: 267-013-3	Fatty acids, C6-C12 Skin Corr. 1C, H314; Eye Dam. 1, H318	≤ 2,5%
CAS: 108-01-0 EINECS: 203-542-8 Index number: 603-047-00-0	2-dimethylaminoethanol Flam. Liq. 3, H226 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	≤ 2,5%

· **Additional information:**

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.  
For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Irritant to skin and mucous membranes.

Strong irritant with the danger of severe eye injury.

· **Hazards**

Causes serious eye damage.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

May be harmful if inhaled.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.

## SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 5)

## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 4)

- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information** No further relevant information available.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Pick up mechanically.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable receptacles.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Prevent formation of aerosols.  
Use only in well ventilated areas.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidising agents.  
Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 6)

## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

Trade name: Super Lube® Fire Resistant Hydraulic Fluid

(Contd. of page 5)

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### 107-21-1 ethanediol

IOELV (EU)	Short-term value: 104 mg/m <sup>3</sup> , 40 ppm Long-term value: 52 mg/m <sup>3</sup> , 20 ppm Skin
TLV (USA)	Long-term value: NIC-10* mg/m <sup>3</sup> Ceiling limit: (100) mg/m <sup>3</sup> (H);*as inhalable fraction and vapor
EL (Canada)	Short-term value: 20** mg/m <sup>3</sup> Long-term value: 10** mg/m <sup>3</sup> Ceiling limit: 100* mg/m <sup>3</sup> , 50*** ppm *Aerosol; **Particulate; ***Vapour
EV (Canada)	Ceiling limit: 100 mg/m <sup>3</sup>

##### 111-46-6 2,2'-oxybisethanol

WEEL (USA)	Long-term value: 10 mg/m <sup>3</sup>
------------	---------------------------------------

##### 108-01-0 2-dimethylaminoethanol

EV (Canada)	Short-term value: 22 mg/m <sup>3</sup> , 6 ppm Long-term value: 11 mg/m <sup>3</sup> , 3 ppm
-------------	---

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

#### · Respiratory protection:

Not required under normal conditions of use.  
For spills, respiratory protection may be advisable.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 6)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Contact lenses should not be worn.



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Red

- **Odour:** Mild

- **Odour threshold:** Not determined.

- **pH-value at 20 °C (68 °F):** 9,2

- **Change in condition**

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: >100 °C (>212 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Auto/Self-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapour pressure:** Not determined.

- **Density at 20 °C (68 °F):** 1 g/cm<sup>3</sup> (8,345 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

(Contd. on page 8)

# Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

Trade name: Super Lube® Fire Resistant Hydraulic Fluid

- **Solubility in / Miscibility with water:** Fully miscible. (Contd. of page 7)
- **Partition coefficient (n-octanol/water):** Not determined.
- **Solvent content:**
- **VOC (California)** <1%
- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic:** Not determined.
- **9.2 Other information** No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Reacts with strong alkali.  
Reacts with strong acids and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values relevant for classification:</b>		
<b>107-21-1 ethanediol</b>		
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	9530 mg/kg (rabbit)
<b>111-46-6 2,2'-oxybisethanol</b>		
Oral	LD50	12565 mg/kg (rat)
Dermal	LD50	11890 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Strong irritant with the danger of severe eye injury.

- **Sensitisation:** No sensitising effects known.

- **Subacute to chronic toxicity:**

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 9)



## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 8)

Harmful

Toxic and/or corrosive effects may be delayed up to 24 hours.

- **Acute effects (acute toxicity, irritation and corrosivity):**

Irritating to skin.

Causes serious eye damage.

- **Repeated dose toxicity:**

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):** See Section 15.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

- **14.1 UN-Number**

- **DOT, ADR, ADN, IMDG, IATA**

Not Regulated

- **14.2 UN proper shipping name**

- **DOT, ADR, ADN, IMDG, IATA**

Not Regulated

(Contd. on page 10)

## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

Trade name: Super Lube® Fire Resistant Hydraulic Fluid

(Contd. of page 9)

- **14.3 Transport hazard class(es)**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Not Regulated
- **14.4 Packing group**
- **DOT, ADR, IMDG, IATA** Not Regulated
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

107-21-1 | ethanediol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

107-21-1 | ethanediol

A4

(Contd. on page 11)

## Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 10)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

107-21-1 | ethanediol

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

# Safety Data Sheet

according to (EU) 2015 / 830 and OSHA GHS

Revision: August 17, 2017

**Trade name: Super Lube® Fire Resistant Hydraulic Fluid**

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
HMIS: Hazardous Materials Identification System (USA)  
WHMIS: Workplace Hazardous Materials Information System (Canada)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B  
Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

**Sources**

SDS Prepared by:  
ChemTel Inc.  
1305 North Florida Avenue  
Tampa, Florida USA 33602-2902  
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
Website: [www.chemtelinc.com](http://www.chemtelinc.com)