

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (PTFE) (aerosol)

(Contd. of page 7)

- **Flash point:** Extremely flammable aerosol.
- **Flammability (solid, gaseous):** Extremely flammable aerosol.
- **Auto/Self-ignition temperature:** 210 °C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - Lower:** 1,1 Vol %
 - Upper:** 7,0 Vol %
- **Vapour pressure:** Not determined.
- **Density:** Not determined.
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - VOC (California)** < 25%
 - Exempt VOCs are excluded from this value
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Danger of receptacles bursting because of high vapour pressure when heated.
- **10.3 Possibility of hazardous reactions**
Develops readily flammable gases/fumes.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Extremely flammable aerosol.
Used empty containers may contain product gases which form explosive mixtures with air.
Reacts with strong oxidising agents.
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Keep away from heat and direct sunlight.
Store away from oxidising agents.

(Contd. on page 9)

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Synolon® (PTFE) (aerosol)

(Contd. of page 8)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-47-8 Distillates (petroleum), hydrotreated light

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

142-82-5 heptane

Oral	LD50	> 5000 mg/kg (rat) (Estimate)
Inhalative	LC50/4h	103 mg/l (rat)

Primary irritant effect:

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitisation:** No sensitising effects known.

Additional toxicological information:

Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Acute effects (acute toxicity, irritation and corrosivity):

Vapours have narcotic effect.

Irritating to skin.

May be fatal if swallowed and enters airways.

· **Repeated dose toxicity:** May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1 Toxicity

· **Aquatic toxicity:** Toxic for aquatic organisms

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

Ecotoxicological effects:

· **Remark:** Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 10)

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (PTFE) (aerosol)

(Contd. of page 9)



Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water



- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Contact waste processors for recycling information.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
-  Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).
- **DOT** Aerosols, flammable
- **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- **IMDG** AEROSOLS (HEPTANES), MARINE POLLUTANT
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **DOT**
- 
- **Class** 2.1
- **Label** 2.1

- **ADR**
- 

- **Class** 2.1 5F

(Contd. on page 11)

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (PTFE) (aerosol)

(Contd. of page 10)

· **Label** 2.1

· **IMDG**



· **Class** 2.1

· **Label** 2.1

· **IATA**



· **Class** 2.1

· **Label** 2.1

· **14.4 Packing group**

· **DOT, ADR, IMDG, IATA** Not Regulated

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances: heptane

· **Marine pollutant:** Yes

Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user** Not applicable.

· **Danger code (Kemler):** -

· **EMS Number:** F-D,S-U

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category** 2

· **Tunnel restriction code** D

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

(Contd. on page 12)

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Synolon® (PTFE) (aerosol)

(Contd. of page 11)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Carcinogenic Categories**

- **IARC (International Agency for Research on Cancer)**

9002-84-0	Polytetrafluoroethylene	3
-----------	-------------------------	---

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
 Press. Gas L: Gases under pressure: Liquefied gas
 Flam. Liq. 2: Flammable liquids, Hazard Category 2

(Contd. on page 13)

Safety data sheet

according to (EU) 2015 / 830

Revision: September 9, 2016

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (PTFE) (aerosol)

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com