



Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Page: 1/13

Revision: September 1, 2023

1 Identification

Product identifier

Trade name: **Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)**

Article number: No other identifiers

Recommended use and restriction on use

Recommended use: Lubricant

Restrictions on use: See Sections 8 and 10 for further information.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Synco Chemical Corporation
24 DaVinci Dr., P.O. Box 405
Bohemia, NY 11716
Telephone: 631-567-5300
Email: info@super-lube.com

Emergency telephone number:

ChemTel
1-800-255-3924 (US/Canada), 1-813-248-0585 (International), 1-300-954-583 (Australia),
0-800-591-6042 (Brazil), 400-120-0751 (China), 000-800-100-4086 (India), 800-099-0731 (Mexico)

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS02 GHS04 GHS07 GHS08

Signal word: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 1)

H336 May cause drowsiness or dizziness.

H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves/protective clothing/eye protection.

P271 Use only outdoors or in a well-ventilated area.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

NFPA ratings (scale 0 - 4)


Health = 2

Fire = 4

Reactivity = 3

HMIS-ratings (scale 0 - 4)


HEALTH *2 Health = *2

FIRE 4 Fire = 4

REACTIVITY 3 Reactivity = 3

* - Indicates a long term health hazard from repeated or prolonged exposures.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Components:

110-54-3	n-hexane	Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
74-98-6	propane	Flam. Gas 1, H220 Press. Gas, H280	25-50%
106-97-8	butane	Flam. Gas 1, H220 Press. Gas, H280	25-50%
124-38-9	carbon dioxide	Press. Gas, H280	2.5-10%

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 2)

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
In cases of frostbite, rinse with plenty of water. Do not remove clothing.

· **After eye contact:**

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Unlikely route of exposure.
Rinse out mouth and then drink plenty of water.
A person vomiting while lying on their back should be turned onto their side.
Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache
Breathing difficulty
Frostbite
Dizziness
Coughing
Irritant to skin and mucous membranes.
Slight irritant effect on eyes.

· **Danger:**

Vapors have narcotic effect.
Danger of disturbed cardiac rhythm.
Danger of impaired breathing.
May cause neurotoxic effects.
Suspected of damaging fertility or the unborn child.

· **Indication of any immediate medical attention and special treatment needed:**

Later observation for pneumonia and pulmonary edema.
Treat frost-bitten areas appropriately.
If swallowed or in case of vomiting, danger of entering the lungs.
Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Alcohol resistant foam
 - Carbon dioxide
 - Fire-extinguishing powder
 - Gaseous extinguishing agents
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture**
 - Formation of toxic gases is possible during heating or in case of fire.
 - Danger of receptacles bursting because of high vapor pressure if heated.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:**
 - Eliminate all ignition sources if safe to do so.
 - Cool endangered containers with water fog.
 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Ensure adequate ventilation.
 - Wear protective equipment. Keep unprotected persons away.
 - Keep away from ignition sources.
 - Protect from heat.
- **Environmental precautions**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
 - Allow to evaporate.
 - Absorb liquid components with non-combustible liquid-binding material.
 - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
 - Open and handle receptacle with care.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 4)

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Emergency cooling must be available in case of nearby fire.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

· **Further information about storage conditions:**

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Storage Temperatures : <122 °F / <50 °C.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-54-3 n-hexane

PEL (USA) Long-term value: 1800 mg/m³, 500 ppm

REL (USA) Long-term value: 180 mg/m³, 50 ppm

TLV (USA) Long-term value: 176 mg/m³, 50 ppm
Skin; BEI

EL (Canada) Long-term value: 20 ppm
Skin

EV (Canada) Long-term value: 176 mg/m³, 50 ppm

LMPE (Mexico) Long-term value: 50 ppm
PIEL, IBE

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; NIC-EX

EL (Canada) Long-term value: 1000 ppm

EV (Canada) Long-term value: 1000 ppm

LMPE (Mexico) Long-term value: 1000 ppm

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 5)

106-97-8 butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: (2370) mg/m ³ , (1000) ppm NIC-EX
EL (Canada)	Short-term value: 750 ppm Long-term value: 600 ppm
EV (Canada)	Long-term value: 800 ppm
LMPE (Mexico)	Long-term value: 1000 ppm

124-38-9 carbon dioxide

PEL (USA)	Long-term value: 9000 mg/m ³ , 5000 ppm
REL (USA)	Short-term value: 54.000 mg/m ³ , 30.000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
TLV (USA)	Short-term value: 54.000 mg/m ³ , 30.000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
EL (Canada)	Short-term value: 15000 ppm Long-term value: 5000 ppm
EV (Canada)	Short-term value: 54000 mg/m ³ , 30000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
LMPE (Mexico)	Short-term value: 30000 ppm Long-term value: 5000 ppm

· **Ingredients with biological limit values:**

110-54-3 n-hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis
-----------	---

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· **Engineering controls:** No relevant information available.

· **Breathing equipment:**

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:**

Not required under normal conditions of use.

Protection may be required for spills.

- **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Aerosol

Color: Transparent

- **Odor:** Solvent-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Melting point/Melting range:** Not applicable, as aerosol.

- **Boiling point/Boiling range:** Not applicable, as aerosol.

- **Flash point:** -104 °C (-155 °F)
Extremely flammable aerosol.

- **Flammability (solid, gaseous):** Not applicable.

- **Auto-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

- **Explosion limits**

Lower: Not determined.

Upper: Not determined.

- **Oxidizing properties:** Not determined.

- **Vapor pressure at 20 °C (68 °F):** 5.0-5.5 bar

- **Density:**

Relative density: Not determined.

Vapor density: Not determined.

Evaporation rate: Not applicable.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 7)

- | | |
|----------------------------|------------------------------------|
| · Viscosity | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| VOC (California): | Exempt |
| · Other information | No relevant information available. |

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- **Possibility of hazardous reactions**
Extremely flammable aerosol.
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.
Develops readily flammable gases / fumes.
Danger of receptacles bursting because of high vapor pressure if heated.
Reacts with peroxides and other radical forming substances.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizing agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Slight irritant effect on eyes.
- **Sensitization:** No sensitizing effects known.
- **Subacute to chronic toxicity:**
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 8)

- **Probable route(s) of exposure:**
Inhalation.
Eye contact.
Skin contact.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Repr. 2
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:**
May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure:
Inhalation.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Toxic for aquatic organisms
- **Persistence and degradability** The organic portion of the product is biodegradable.
- **Bioaccumulative potential:** Does not accumulate in organisms
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information**
- **General notes:**
This statement was deduced from the properties of the single components.
Do not allow product to reach ground water, water course or sewage system.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 9)

- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950

- **UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

- **DOT** Aerosols
- **ADR** AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- **IMDG** AEROSOLS, MARINE POLLUTANT
- **IATA** Aerosols, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1

- **ADR**



- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG**



- **Class** 2.1
- **Label** 2.1

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 10)

· IATA



· Class	2.1
· Label	2.1

· Packing group	Aerosols are not assigned a packing group.
-----------------	--

· Environmental hazards	Product contains environmentally hazardous substances: n-hexane
· Marine pollutant:	Yes Symbol (fish and tree)

· Special precautions for user	Warning: Gases
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
---	-----------------

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

110-54-3	n-hexane
----------	----------

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

74-98-6	propane	10000
106-97-8	butane	10000

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 11)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

110-54-3 | n-hexane

||

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 12/23/2016 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LDLo: Lowest Lethal Dose Observed

Flam. Gas 1: Flammable gases – Category 1

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Press. Gas: Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

(Cont'd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Revision: September 1, 2023

Trade name: Super Lube® Dri-Film Lubricant with Syncolon® (aerosol)

(Cont'd. of page 12)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com